


## FANUC Robot M-3iA




### FEATURES

FANUC Robot M-3iA is a large-sized parallel link robot for high speed picking and assembly. The exclusive 6 axes type of parallel link robot expanded robotization of transferring and assembling application.

- Three models are available to meet a variety of applications.
  - FANUC Robot M-3iA/6S  
Total 4 axes robot including single axis rotation at wrist. The maximum payload is 8kg (option), suitable for high speed arranging and handling of multi work pieces at the same time on the conveyor.
  - FANUC Robot M-3iA/6A  
Total 6 axes robot including three rotation axes at wrist. This model can change wrist direction freely and suitable for assembling application.
  - FANUC Robot M-3iA/12H  
Total 3 axes and 12kg payload robot without rotation axes at wrist. This model is suitable for high speed picking of plenty work pieces on the conveyor.
- IP67 of enclosed mechanical unit realized reliable water and dust proof ability.
- Food adaptation option is available that adopts suitable material, high durability surface treatment and food grade lubricant. It will progress robotization of food market.
- Various intelligent functions are available, such as iRVision (integrated vision) and iRPickTool.

### Application Examples




Standing the bottles by M-3iA/6A




High speed arranging the foods by M-3iA/6S

## Operating space


### M-3iA/6S



### M-3iA/6A



### M-3iA/12H



## Specifications

Model	M-3iA/6S	M-3iA/6A	M-3iA/12H
Type	Parallel link mechanism		
Controlled axes	4 axes (J1, J2, J3, J4)	6axes (J1, J2, J3, J4, J5, J6)	3axes (J1, J2, J3)
Installation	Ceiling mount		
Motion range	Diameter 1,350 mm, height 500 mm Note 4)		
(Maximum speed)	J1-J3	720° (2000°/s) 12.57 rad (34.90 rad/s)	—
Note 1)	J4	300° (2000°/s) 5.24 rad (34.90 rad/s)	—
	J5	720° (2000°/s) 12.57 rad (34.90 rad/s)	—
	J6	—	—
Max.payload at wrist	6 kg (8 kg with an option)	6 kg	12 kg
Repeatability Note 2)	±0.03 mm		
Drive method	Electric servo drive by AC servo motor		
Mass Note 3)	160 kg	175 kg	155 kg
Installation environment	Ambient temperature : 0 to 45°C Ambient humidity Normally : 75%RH or less (No dew, nor frost allowed) Short term : Max. 95%RH or less (within one month) Vibration : 4.9m/s <sup>2</sup> (0.5G) or less		

Note 1) During short distance motions, the axis speed doesn't reach maximum one.

Note 2) Compliant with ISO9283.

Note 3) Without controller.

Note 4) For M-3iA/6S and M-3iA/12H, in case the payload is larger than 6 kg, there is a limitation on the work envelope.

# FANUC CORPORATION

•Headquarters Oshino-mura, Yamanashi 401-0597, Japan  
Phone: 81-555-84-5555 Fax: 81-555-84-5512 <http://www.fanuc.co.jp>

•Overseas Affiliated Companies  
FANUC America Corporation  
FANUC Europe Corporation, S.A.  
SHANGHAI-FANUC Robotics CO., LTD.  
KOREA FANUC CORPORATION  
TAIWAN FANUC CORPORATION  
FANUC INDIA PRIVATE LIMITED  
FANUC SINGAPORE PTE. LTD.  
FANUC THAI LIMITED  
FANUC MECHATRONICS (MALAYSIA) SDN. BHD.

PT. FANUC INDONESIA  
FANUC OCEANIA PTY. LIMITED  
FANUC SOUTH AFRICA (PROPRIETARY) LIMITED

3900 West Hamlin Road, Rochester Hills, MI 48309-3253, U.S.A.  
Zone Industrielle, L-6468 Echternach, Grand-Duché de Luxembourg  
No. 1500 Fulian Road, Baoshan Area, Shanghai, China  
101, Wanam-ro(st), Seongsan-gu, Changwon-si, Gyeongsangnam-do, 642-290 Republic of Korea  
No.10, 16th Road, Taichung Industrial Park, Taichung, Taiwan  
41-A, Electronics City, Bangalore, 560 100, India  
No.1 Teban Gardens Crescent, Singapore 608919, Singapore  
1301 Pattanakarn Road, Kwaeng Suanluang, Khet Suanluang, Bangkok 10250 Thailand  
No.32, Jalan Pengacara U1/48, Temasya Industrial Park, Section U1, Glenmarie,  
40150 Shah Alam, Selangor Darul Ehsan, Malaysia  
JL. Boulevard Bukit Gading Raya Blok R, Jakarta 14240 Indonesia  
10 Healey Circuit, Huntingwood, NSW 2148, Australia  
17 Loper Ave. Aeroport Industrial Estd. Spartan Ext.2 P.O.Box 219, Isando 1600, Republic of South Africa

Phone: 1-248-377-7000 Fax: 1-855-774-7051  
Phone: 352-727777-1 Fax: 352-727777-403  
Phone: 86-21-5032-7700 Fax: 86-21-5032-7711  
Phone: 82-55-278-1200 Fax: 82-55-284-9826  
Phone: 886-4-2359-0522 Fax: 886-4-2359-0771  
Phone: 91-80-2852-0057 Fax: 91-80-2852-0051  
Phone: 65-6567-8566 Fax: 65-6566-5937  
Phone: 66-2-714-6111 Fax: 66-2-714-6120

Phone: 60-3-7628-0110 Fax: 60-3-7628-0220  
Phone: 62-21-4584-7285 Fax: 62-21-4584-7288  
Phone: 61-2-8822-4600 Fax: 61-2-8822-4666  
Phone: 27-11-392-3610 Fax: 27-11-392-3615

•All specifications are subject to change without notice.  
•No part of this catalog may be reproduced in any form.  
•The products in this catalog are controlled based on Japan's "Foreign Exchange and Foreign Trade Law". The export from Japan may be subject to an export license by the government of Japan. Further, re-export to another country may be subject to the license of the government of the country from where the product is re-exported. Furthermore, the product may also be controlled by re-export regulations of the United States government. Should you wish to export or re-export these products, please contact FANUC for advice.

© FANUC CORPORATION, 2009  
RM-3iA(E)-07a, 2019.4, Printed in Japan